

better together

EC Declaration of Performance DRAMIX® RC - 80/30 - CP

CUSTOMER **INFORMATION**

- 1. Unique identification code of the product: DRAMIX® RC 80/30 CP
- 2. Type- and traceability info, allowing identification of the construction product as required pursuant to Article 11(4): is provided on the product packaging and product label.
- 3. Intended use of the construction product in accordance with EN 14889-1: 2006. DRAMIX® RC - 80/30 - CP are steel fibres, made of cold-drawn wire, for STRUCTURAL USE in concrete, mortar and grout.
- 4. Name, registered trade name and contact address of the manufacturer as required pursuant to Article 11(5): NV BEKAERT SA Bekaertstraat 2, B-8550 Zwevegem, Belgium.
- 5. Not applicable.
- 6. System of assessment and verification of constancy of performance of the construction product: System n°1
- 7. Notified Certification Body:

BCCA - registration nr: 0749 / B-1040 Brussel, Rue d' Arlon, 53 has performed under System n°1

- determination of the product-type on the basis of Type Testing.
- initial inspection of the manufacturing plant and of Factory Production Control
- continuous surveillance, assessment and evaluation of Factory Production Control issued: a 'certificate of constancy of performance' per product or plant - see table 2.

Notified Labs:

WTCB - registration nr: 1136 / B-1000 Brussel, Lombardstraat 42 performed: Initial Type Testing and issued ITT reports – see table 2.

- 8. Not applicable.
- 9. Declared performance: the essential characteristics per product type are listed in table 1.
- 10. The performance of the products identified in points 1 and 2 and listed in table 1, are in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Paul De Geyter, Global Quality manager NV Bekaert SA



Approved by: Global Quality manager Bekaert Paul De Geyter

Issued and signed on version date, Zwevegem-Belgium





Disclaimer: This Customer Information shall not constitute a guarantee for any specific product features. Final determination of suitability of this material is the sole responsibility of the user.

DOP CI.0001.BKZW/Version-2: 2017/06/29

Replaces: 1- 2016/11/09

Creationdate 2017/09/07 - Language EN **Electronically approved**

Building Products//Geert Demeyere/ Jan Kiska



better together

EC Declaration of Performance DRAMIX® RC - 80/30 - CP

CUSTOMER INFORMATION

Addendum to pt 9. Declared Performance on essential characteristics – see table 1 in accordance with EN 14889-1: 2006.

Table 1: Declaration on essential characteristics		
Product type	DRAMIX® RC - 80/30 - CP	
EC Certificate of constancy of performance Issued by notified body	BC1-251-0024-0010-002	
Fibre shape	Hooked ends	
Bundling	Glued	
Coating	Zinc	
Length (mm)	30	
Diameter (mm)	0,38	
Aspect Ratio	79	
Tensile Strength (N/mm²)	3070	
Effect on consistence (s)	8	
Effect on strength of concrete (kg/m³)	25	
Release of dangerous substances	No	
Durability	NPD	
Modulus of elasticity (GPa)	200	

Addendum to pt 7. Reports issued under surveillance of Notified body – see table 2

Table 2: related ITT reports		
Characteristic	ITT - Report reference	Origin of Report
ITT - Effect on Consistency	DE 611XB 068/7	WTCB
ITT - Effect on strength of concrete	DE 611 XB 068/6	WTCB
ITT - Tensile Strength	651 XG 552 - CAR 8056-1	WTCB

Disclaimer: This Customer Information shall not constitute a guarantee for any specific product features. Final determination of suitability of this material is the sole responsibility of the user.

Building Products//Geert Demeyere/ Jan Kiska