

DOP_CI.0001.BKZW/Version-2: 2017/06/29 Replaces: 1- 2016/11/09 Creationdate 2017/09/07 – Language EN Electronically approved Building Products//Geert Demeyere/ Jan Kiska

Page 1/2

Off-line or printed copy is uncontrolled !

BEKAERT

better together

EC Declaration of Performance DRAMIX® RC - 90/35 - BP

CUSTOMER INFORMATION

Addendum to pt 9. Declared Performance on essential characteristics – see table 1 in accordance with EN 14889-1: 2006.

Table 1: Declaration on essential characteristics		
Product type	DRAMIX® RC - 90/35 - BP	
EC Certificate of constancy of performance Issued by notified body	BC1-251-0024-0058-002	
Fibre shape	Hooked ends	
Bundling	Glued	
Coating	-	
Length (mm)	35	
Diameter (mm)	0,38	
Aspect Ratio	92	
Tensile Strength (N/mm ²)	3070	
Effect on consistence (s)	8	
Effect on strength of concrete (kg/m ³)	15	
Release of dangerous substances	No	
Durability	NPD	
Modulus of elasticity (GPa)	200	

Addendum to pt 7. Reports issued under surveillance of Notified body - see table 2

Table 2: related ITT reports		
Characteristic	ITT - Report reference	Origin of Report
ITT - Effect on Consistency	DE 611XB 068/7	WTCB
ITT - Effect on strength of concrete	-	WTCB
ITT - Tensile Strength	651 XG 552 - CAR 8056-1	WTCB

Disclaimer: This Customer Information shall not constitute a guarantee for any specific product features. Final determination of suitability of this material is the sole responsibility of the user.