

better together

EC Declaration of Performance Synmix® SP 55

CUSTOMER INFORMATION

- 1. Unique identification code of the product: Synmix® SP 55
- 2. Intended use: Synmix® SP 55 are polymer fibres for OTHER USES in concrete, mortar and grout. (class II - macro fibres)
- 3. Manufacturer: NV BEKAERT SA Bekaertstraat 2, B-8550 Zwevegem, Belgium
- 5. System of assessment and verification of constancy of performance of the construction product: System n°3
- 6a. Harmonized Standard: EN 14889-2: 2006

Notified Body:

TSUS - registration nr: 1301 / SK-821 04 Bratislava, Studená 3

7. Declared performance: the essential characteristics per product type are listed in table 1.

The performance of the products above and listed in table 1, is in conformity with the declared performance in point 7.

This declaration of performance is issued, in accordance with regulation (EU) N°305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Tom Hautekiet, Vice President Building Products - NV Bekaert SA



Approved by: Tom Hautekiet

Issued and signed on version date, Zwevegem-Belgium





Disclaimer: This Customer Information shall not constitute a guarantee for any specific product features. Final determination of suitability of this material is the sole responsibility of the user

DOP_CI.00010.BKZW/version 2:2019/07/16

Replaces: v1 2018/06/06

Creationdate: 2020/01/30 – Language EN

Page 1/2 **Electronically approved**

Building Products//Geert Demeyere



EC Declaration of Performance Synmix® SP 55

CUSTOMER **INFORMATION**

Addendum to pt 7. Declared Performance on essential characteristics - see table 1

Table 1: Declaration on essential characteristics in accordance with EN 14889-2: 2006	
Product type	Synmix® SP 55
EC Certificate of constancy of performance	-
Fibre shape	corrugated wavy
Bundling	loose
Coating	No
Length (mm)	55
Diameter (mm)	0,85
Aspect Ratio	65
Tensile Strength (N/mm²)	365
Effect on consistence (s)	11
Effect on strength of concrete (kg/m³)	8
Modulus of elasticity (N/mm²)	4800
Polymer Type	class II - macro fibres
Melting point (°C)	165
Point of ignition (°C)	≥ 330
Release of dangerous substances	No
Durability	NPD

Disclaimer: This Customer Information shall not constitute a guarantee for any specific product features. Final determination of suitability of this material is the sole responsibility of the user

Building Products//Geert Demeyere